

Distributed By:

Please contact Airwave or your distributor if you need to measure a gas not listed or need a different measurement range.



Ordering Information

Model	TR4021	TR4022	TR4023	TR4024	TR4025
Input Power	(DC) 12-30 VDC (AC) 24 VAC	(DC) 12-30 VDC	(DC) 12-30 VDC	(DC) 12-30 VDC	(DC) 12-30 VDC
Gas Measured	(CO) Carbon Monoxide 0- 400 ppm (CB) Combustibles 0- 1% by volume (832) R-22, 0- 500 ppm R-134(a) 0-3,000 ppm (826) Ammonia 0- 100 ppm	(CO) Carbon Monoxide 0-200 ppm	(CO) Carbon Monoxide 0-200 ppm (NO ₂) Nitrogen Dioxide 0-10 ppm (H ₂) Hydrogen 0-10,000 ppm (Cl ₂) Chlorine 0-5 ppm (O ₂) Oxygen 0-25% (H ₂ S) Hydrogen Sulfide 0-200 ppm (NH ₃) Ammonia 0-50 ppm	(CB) Combustibles 0-100% LEL - Propane - Butane - Methane/Natural Gas - Hydrogen	(CB) Combustibles 0-100% LEL - Propane - Butane - Methane/Natural Gas - Hydrogen
Specify	Specify Low & High Alarm Set-Point Concentrations		Specify Gas To Be Measured	Specify Gas To Be Measured	(EX) Explosion Proof Specify Gas To Be Measured

Technical Information

Measurement Technology	(SS) Solid State (MOS)	(E) Electrochemical	(E) Electrochemical	(CB) Catalytic Bead	(CB) Catalytic Bead
Output Signal	4-20 mA	4-20 mA	4-20 mA	4-20 mA	4-20 mA
Typical Life	up to 10 years	5 years	12 to 24 months	up to 10 years	up to 10 Years
Features & Characteristics	<ul style="list-style-type: none"> Economical Non Linear Output Cross Sensitive To Other Gases 	<ul style="list-style-type: none"> Economical As Solid State Linear Output Specific/High Accuracy Install In Any J Box 	<ul style="list-style-type: none"> High Accuracy Linear Output Gas Specific 	<ul style="list-style-type: none"> High Accuracy Linear Output Cost Effective for Non-Classified Areas 	<ul style="list-style-type: none"> High Accuracy Linear Output Explosion Proof Enclosure
Typical Applications	CO Enclosed Parking Garages Vehicle Repair Facilities Mail & Courier Depots Propane Forklift Areas Manufacturing Facilities Boiler Rooms Ice Rinks Fire Halls Ref Chiller/Mechanical Rooms CB See Catalytic Bead →	CO Enclosed Parking Garages Vehicle Repair Facilities Mail & Courier Depots Propane Forklift Areas Manufacturing Facilities Boiler Rooms Ice Rinks Fire Halls	NO ₂ Parking Structures Loading Docks (Diesel) Diesel Repairs Facilities Manufacturing Facilities H ₂ Battery Charging/Storage Cl ₂ Water Treatment H ₂ S Water Treatment O ₂ Inert Gas Storage MRI Rooms NH ₃ Cold Storage/Refrigeration	CB Parking Structures Propane Storage Facilities Manufacturing Facilities Boiler Rooms Propane Forklift Areas Landfill Sites Combustible Storage Battery Charging/Storage Non-Classified Areas	CB Propane Storage Facilities Manufacturing Facilities Combustible Storage Class 1, Div 1 Areas

See Over For Airwave Gas Controller Options

Distributed By:

Please contact Airwave or your distributor if you need to measure a gas not listed or need a different measurement range.



Integrated SS



Use With Transmitters



Dual Channel Controller



Customizable Multiple Point Controller

Single Channel Controller

Ordering Information

Model	AE4050	AE4052	AE4001B
Sensor Type	Select Transmitter Or Integrated Solid State <ul style="list-style-type: none"> Solid State - Integrated (SS) or TR4021 Electrochemical select TR4022 or TR4023 Catalytic Bead select TR4024 or TR4025 Infrared CO₂ select TR4026 	Select 2 Gas Sensors Using Transmitter Or Integrated Solid State <ul style="list-style-type: none"> Solid State - Integrated (SS) or TR4021 Electrochemical select TR4022 or TR4023 Catalytic Bead select TR4024 or TR4026 Infrared CO₂ select TR4026 	<ul style="list-style-type: none"> Will work with all Transmitters
Input Power	(12/24 VAC/VDC) (115 VAC) (240 VAC)	(24 VAC) (115 VAC) (240 VAC)	(24 VAC) (115 VAC) (240 VAC)
Select Gas(s) To Be Measured	See Gases Measured in Gas Transmitter Selection Guide	See Gases Measured in Gas Transmitter Selection Guide:	See Gases Measured in Gas Transmitter Selection Guide. Can be designed from 3 to 200 inputs or more.
Options	(H-AC) Remote horn alarm center (SL-AC) Remote strobe alarm center (HSL-AC) Remote horn & strobe alarm center.	(H-S) Horn mounted on AE4052 (SL-S) Strobe mounted on AE4052 (HSL-S) Horn & strobe mounted on AE4052. (H-AC) Remote horn alarm center (SL-AC) Remote strobe alarm center (HSL-AC) Remote horn & strobe alarm center.	List requirements for customized design. Possible Custom Components include: displays, a variety of outputs (inputs, analog, digital), custom control schemes and sequence of operation. Contact Airwave for assistance.
Relays: Specify Low and High Trip Points (TP)	TP1 Low trip point concentration TP2 High trip point concentration	Gas 1 Low trip point measurement value High trip point measurement value Gas 2 Low trip point measurement value High trip point measurement value F1 Fault Alarm Trip Point	Can provide a variety of outputs based on need including relay, analog, or digital signal. Specify control requirements.

Technical Information

Timer On Low Trip Point(s)	Up to 30 min delay on-time, adjustable in 2 minute increments.	Up to 30 min delay on-time, adjustable in 2 minute increments.	Specify requirements
Relay Ratings Features	2 x 5 Amp <ul style="list-style-type: none"> Low Cost Control Solution Possible to Parallel Wire A Number of Controllers Line Voltage or 24 VAC Time Delay 	5 x 10 Amp <ul style="list-style-type: none"> Low Cost Control Solution Possible to Parallel Wire A Number of Controllers Line Voltage or 24 VAC Time Delay Choice Of A Variety Of Sensors 	Specify requirements <ul style="list-style-type: none"> Highly Flexible Platform Variety Of Control And Interface Options Designed To Customer's Specifications For Large Applications

See Over For Airwave Gas Sensors/Transmitters

Specifications Subject To Change Without Notice

June 19, 2007

Airwave Electronics Box 2, Site 18, RR 1; Didsbury, AB TOM 0W0
Tel: (403) 335-9875 / Fax (403) 335-4818 / www.gasdetect.com