

SPECIFICATION SHEET FOR H₂ SENSOR COMPACT

H2-7/1000

Nominal Range 0 – 1000 ppm
 Maximum Overload 2000 ppm
 Expected Operation Life 2 years in air
 Output Signal 30 +/- 10 nA/ppm
 Resolution <1.2 ppm
 Temperature Range - 40 °C to + 50 °C
 Pressure Range Atmospheric +/-10 %
 t₉₀ Response Time < 30 sec
 Relative Humidity Range 15 % to 90 % R.H. non-condensing
 Typical Baseline Range (pure air, 20°C) – 8 ppm to +8 ppm
 Maximum Zero Shift (+20°C to +40 °C) 3.0 ppm equivalent
 Expected Long Term Output Drift < 2 % signal loss/month
 Recommended Load Resistor 10 Ohm
 Bias Voltage Not required
 Repeatability < 2 % of signal
 Output Linearity Linear

Weight ~ 13 g
 Position Sensitivity None
 Storage Life Six months in container
 Recommended Storage Temperature 5 °C – 20 °C
 Warranty Period 12 months from date of dispatch

PERFORMANCE CHARACTERISTICS

CROSS-SENSITIVITY DATA

Interfering Gas Concentration Reading
 CO 100 ppm < 60 ppm

Performance data conditions:
 20 °C, 50% RH and 1013 mbar

APPLICATIONS

Safety and Environmental Control
 For Portable Gas Detectors

